

Concrete lifter



I SAFETY I EASE OF USE I NO DISTORTION

I PRODUCTIVITY INCREASE I COST REDUCTION



Power supply Electrical, diesel, gasoline, hydraulic.

Load capacity Up to 40 tons.

Main component list Vacuum tank, vacuum pump, suction pad, central unit, security components.

Production time 12-14 weeks.

Spare part delivery

conditions Delivery 10-15 days with standard usual spare parts.

Connecting systems Crane, stacker, mobile crane, crane turret, forklift, excavator, side boom, gib,

truck crane, motorized carriage.

Wear parts Suction pad, vacuum hose, pump filter, electro valve, vacuostat, vacuometer.

Options Control of suspended load, camera wireless, remote control.

Handling type possibilities Horizontal, vertical, turning 360°, rotating 360°.

Security system Horning & lighting system, vacuum tank, visual system, battery save signal.


Security parameters Security coefficient 2 & 80% vacuum level guaranteed, holding time increased

from 5 to 20 min.


Country standards ISO 9001, AFNOR EN 13155, DIRECTIVE MACHINE 2006/42/CE.

ACIMEX has the capacity to adjust its production tool to specific country standards.

References: Bonna Sabla, Stradal, Capremib, Alkern, Prefolir, Rector, Sotubema, Chapsol.














Turning 360°

This document shows general features: each product can be adapted as ACIMEX designs turnkey solutions for its clients







